TAGETES II













Recessed luminary TAGETES is a lighting luminary can be installed in a dropped ceiling that is based on T24 grid and is equipped with the most modern highly-efficient LED lighting sources. TAGETES luminary is made out of steel plate which is powder-lacquered white. The distinctive feature of TANGETES is its monolithic construction, which means that this luminary can not disassemble during its exploitation. Two possibilities of the diffuser to choose: PLX or MPRM. TANGETES luminary is recommended to light public buildings, such as universities, schools, offices, public administration buildings and other facilities.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
TAGETES II 24W 596	3681 / 3496	25	4000 / 3000	596 x 596 x 60
TAGETES II 48W 596	7363 / 6992	49	4000 / 3000	596 x 596 x 60

Lighting and electrical parameters:

Light source	LED
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5÷30
Driver	LED driver
DIIVEI	DALI *

Mechanical data:

Material	steel sheet
Color	white
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 18-08-2025

