

ASTER TRANSPARENT



Industrial luminaries ASTER is a ceiling luminaire with highly-efficient LED light sources. It features high ingress protection (IP65) and high protection against mechanical impact (IK10). ASTER luminaire is well-adjusted to dusty rooms or those with elevated humidity. . ASTER luminaries are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -25°C and +30°C.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ASTER PC-T 24W 1200	3900 / 4107	24	3000 / 4000	1190 x 85 x 67
ASTER PC-T 36W 1200	5252 / 5588	36	3000 / 4000	1190 x 85 x 67
ASTER PC-T 48W 1200	7801 / 8215	48	3000 / 4000	1190 x 85 x 67
ASTER PC-T 62W 1200	9253 / 9746	62	3000 / 4000	1190 x 85 x 67
ASTER PRO PC-T 68W 1200	11484	68	4000	1190 x 85 x 67

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50/L80/B10
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	-25 ÷ 30
Driver	DALI Driver LED Driver *

Mechanical data:

Material	polycarbonate
Color	gray
Diffuser	PC transparent polycarbonate

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024