

ASTER C



Industrial luminaries ASTER is a ceiling luminary. It features high ingress protection (IP65) and high protection against mechanical impact (IK08). ASTER luminary is well-adjusted to dusty rooms or those with elevated humidity. ASTER luminaries are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -20°C and +40°C.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ASTER C 40W 1200	4200	40	4000	1190 x 72 x 61
ASTER CC 36W 1200	5040	36	4000	1190 x 72 x 61
ASTER CC 50W 1200	7200	50	4000	1190 x 85 x 67

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	70000
Lx/By	L70/B50
CRI	>80
SDCM	4
Operating temperature range [°C]	-20 - +40
Driver	LED Driver

Mechanical data:

Material	polycarbonate
Color	gray
Diffuser	PC opalized polycarbonate

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024