


ASTER INOX FRZ 600



Industrial luminaries ASTER is a ceiling luminaire with highly-efficient LED light sources. It features high ingress protection (IP66) and high protection against mechanical impact (IK10). ASTER luminaire is well-adjusted to dusty rooms or those with elevated humidity. . ASTER luminaries are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -25°C and +30°C.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ASTER INOX FRZ 4W 600	660 / 632	4	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 6W 600	983 / 912	6.2	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 8W 600	1311 / 1259	8.3	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 12W 600	1952 / 1876	12.7	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 17W 600	2617 / 2513	17.2	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 19W 600	2936 / 2822	19.5	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 21W 600	3268 / 3145	20.9	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 25W 600	3905 / 3753	25.3	4000 / 3000	600 x 100 x 70
ASTER INOX FRZ 29W 600	4589 / 4408	29.7	4000 / 3000	600 x 100 x 70

Lighting and electrical parameters:

Light source	LED
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Operating temperature range [°C]	-20 ÷ 50 / -20 ÷ 40 / -20 ÷ 35
Driver	LED driver

Mechanical data:

Material	polycarbonate
Color	gray
Diffuser	PC frosted polycarbonate

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 18-08-2025