

ASTER OPAL



Industrial luminaries ASTER is a ceiling luminaire with highly-efficient LED light sources. It features high ingress protection (IP65) and high protection against mechanical impact (IK10). ASTER luminaire is well-adjusted to dusty rooms or those with elevated humidity. . ASTER luminaries are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -25°C and +30°C.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ASTER OPAL 24W 1200	3383 / 3562	24	3000 / 4000	1190 x 85 x 67
ASTER OPAL 36W 1200	4556 / 4846	36	3000 / 4000	1190 x 85 x 67
ASTER OPAL 48W 1200	6766 / 7125	48	3000 / 4000	1190 x 85 x 67
ASTER OPAL 62W 1200	7719 / 8300	62	3000 / 4000	1190 x 85 x 67
ASTER OPAL 31W 1500	4192 / 4417	31	3000 / 4000	1480 x 85 x 67
ASTER OPAL 12W 600	1744	12	4000	600 x 85 x 67
ASTER OPAL 15W 600	2031	15	4000	600 x 85 x 67
ASTER OPAL 25W 600	3488	25	4000	600 x 85 x 67
ASTER OPAL 30W 600	4061	30	4000	600 x 85 x 67

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	-25 ÷ 30
Driver	DALI Driver LED Driver *

Mechanical data:

Material	polycarbonate
Color	gray
Diffuser	PC opalized polycarbonate

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024