


ASTER PRO OPT



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ASTER PRO OPT-HR 64W 1200	8495	64	4000	1190 x 85 x 67
ASTER PRO OPT-HR 56W 1200	7646	56	4000	1190 x 85 x 67
ASTER PRO OPT-HR 43W 1200	6043	43	4000	1190 x 85 x 67
ASTER PRO OPT-HR 30W 1200	4362	30	4000	1190 x 85 x 67
ASTER PRO OPT-HR 17W 1200	2640	17.6	4000	1190 x 85 x 67
ASTER PRO OPT-60 64W 1200	8495	64	4000	1190 x 85 x 67
ASTER PRO OPT-60 56W 1200	7646	56	4000	1190 x 85 x 67
ASTER PRO OPT-60 43W 1200	6043	43	4000	1190 x 85 x 67
ASTER PRO OPT-60 30W 1200	4362	30	4000	1190 x 85 x 67
ASTER PRO OPT-60 17W 1200	2640	17.6	4000	1190 x 85 x 67
ASTER PRO OPT-RS 64W 1200	8495	64	4000	1190 x 85 x 67
ASTER PRO OPT-RS 56W 1200	7646	56	4000	1190 x 85 x 67
ASTER PRO OPT-RS 43W 1200	6043	43	4000	1190 x 85 x 67
ASTER PRO OPT-RS 30W 1200	4362	30	4000	1190 x 85 x 67
ASTER PRO OPT-RS 17W 1200	2640	17.6	4000	1190 x 85 x 67

Lighting and electrical parameters:

Light source	LED
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	120000/150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver DALI driver *

Mechanical data:

Material	polycarbonate
Color	gray
Diffuser	PC transparent polycarbonate

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025