



Surface-mounted luminaire CROCUS is made out of white powder-lacquered steel plate. The CROCUS MW luminaire is equipped with a multi-range power supply (MultiWatt), thanks to which the installer can select the power of the luminaire when connecting the luminaire, so the same luminaire can be used for many solutions, with several flux/power levels. The polymethyl methacrylate luminaire's shade is opalized.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
CROCUS MW 1255	#VALUE!	24 – 36	4000	1193 x 207 x 68
CROCUS 24W 1255	3245 / 3417	24	3000 / 4000	1193 x 207 x 68
CROCUS 36W 1255	4369 / 4648	36	3000 / 4000	1193 x 207 x 68
CROCUS 48W 1255	6489 / 6834	48	3000 / 4000	1193 x 207 x 68
CROCUS 72W 1255	8739 / 9296	72	3000 / 4000	1193 x 207 x 68

Lighting and electrical parameters:

Light source	LED/LED DALI
Voltage	220–240 V, 50–60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver MultiWatt LED Driver DALI Driver *

Mechanical data:

Material	steel sheet
Color	white
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024