



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
DAISY PRO P MW 600	2034 - 6703 / 2148 - 7088 / 1912 - 6301	12,6 - 45,3 / 12,7 - 45,3	4000 / 3000	596 x 596 x 34
DAISY PRO P MPRM 600	6703 / 6416 / 6099 / 5807 / 5512 / 5185 / 4560 / 3948 / 3323 / 2685 / 2034 / 4871 - 6703	45.3 / 43.1 / 40.7 / 38.5 / 36.3 / 34 / 29.6 / 25.4 / 21.2 / 17 / 12.6 / 31,8 - 45,3	4000	596 x 596 x 34
DAISY PRO P PLX 600	7088 / 6784 / 6423 / 6116 / 5805 / 5476 / 4816 / 4169 / 3509 / 2835 / 2148 / 5145 - 7088	45.3 / 43.1 / 40.7 / 38.5 / 36.3 / 34 / 29.6 / 25.4 / 21.2 / 17 / 12.6 / 31,8 - 45,3	4000	596 x 596 x 34

Lighting and electrical parameters:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	MultiWatt driver LED driver *

Mechanical data:

Material	aluminum
Color	white
Diffuser	MPRM microprism PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 21-10-2025