



Recessed luminaire DAISY is a modernistic LED panel intended for mounting in the dropped ceiling (with the help of additional accessories directly on ceilings) or as suspended. DAISY luminaire is made out of aluminium which is lacquered white. DAISY has highly-efficient LED light sources and its diffuser is available in variants: PLX or MPRM. The recommended usage of DAISY is among others: public buildings, schools, universities or public administration facilities.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
DAISY PLX IP20/44 600	5085 / 4805 / 4079 / 4285	41 / 38 / 32 / 33.8	4000	595 x 595 x 29
DAISY PLX IP20/65 600	5085 / 4079	41 / 32	4000	596 x 596 x 29 / 595 x 595 x 29

Lighting and electrical parameters:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	70000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver LED driver *

Mechanical data:

Material	aluminium
Color	white
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024