



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
DAISYR PLX 600	4022 / 4117 / 4086 / 4446 / 4312 / 36 / 38 / 33.3 / 37.3 / 35.4 4824	/ 41.7	3000 / 4000	595 x 595 x 10 / 595 x 595 x 25
DAISYR MPRM 600	4065 / 4711 / 4208 / 4344	37.9 / 42.4 / 35.9	4000	595 x 595 x 25
DAISYR MPRM 1200x300	4065 / 4208 / 3944 / 4344 / 4711	37.9 / 35.9 / 33.8 / 42.4	4000	1195 x 295 x 25

Lighting and electrical parameters:

Light source	LED
Voltage	220..240 V, 50..60 Hz/220-240 V, 50-60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
CRI	>80
SDCM	5
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver *

Mechanical data:

Material	aluminium
Color	white
Diffuser	PLX opalized MPRM microprism

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024