



Surface-mounted luminaire FREESIA O is equipped with the highly-efficient LED light sources. The body of the product is made from white powder-lacquered steel plate.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
FREESIA O 13W D300	1519 / 1588	13	3000 / 4000	ø300 x 65
FREESIA O 18W D300	2206 / 2291	18	3000 / 4000	ø300 x 65
FREESIA O 28W D300	3013 / 3150	28	3000 / 4000	ø300 x 65
FREESIA O 22W D500	2839 / 2640	22.5	4000 / 3000	ø475 x 65
FREESIA O 30W D500	3933 / 3658	30.5	4000 / 3000	ø475 x 65
FREESIA O 30W D600	3933 / 3658	30.5	4000 / 3000	ø600 x 65
FREESIA O 55W D600	6588 / 6949	55	3000 / 4000	ø600 x 65

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000/60000
Lx/By	L80/B10
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED driver

Mechanical data:

Material	aluminum
Color	black white *
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 01-08-2025