



FREESIA HONEYCOMB GK



Recessed-mounted luminairesFREESIA HONEYCOMB is equipped with the highly-efficient LED light sources. The body of the product is made from white powder-lacquered steel plate.

Parameters:

| Name | Luminaire luminous flux [lm] | Power of luminaire [W] | Color [K] | Dimensions D x H [mm] |
|------------------------------|------------------------------|------------------------|-------------|-----------------------|
| FREESIA HONEYCOMB GK 13W 33I | 1519 / 1588 | 13 | 3000 / 4000 | 330 x 85 |
| FREESIA HONEYCOMB GK 18W 33I | 2206 / 2291 | 18 | 3000 / 4000 | 330 x 85 |
| FREESIA HONEYCOMB GK 28W 33I | 3013 / 3150 | 28 | 3000 / 4000 | 330 x 85 |

Lighting and electrical parameters:

| | |
|---|--------------------------|
| Light source | LED |
| Voltage | 220-240V, 50-60Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| CRI | >80 |
| SDCM | 3 |
| Photobiological risk class | RG0 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | LED driver |

Mechanical data:

| | |
|--------------|--------------------------------|
| Material | aluminum |
| Color | black white * |
| Diffuser | PLX opalized |

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025