



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
FUCHSIA ALU 20W 625	2100	20	4000	625 x 51 x 102
FUCHSIA ALU 40W 625	4200	40	4000	625 x 51 x 102
FUCHSIA ALU 40W 1225	4200	40	4000	1204 x 51 x 102
FUCHSIA ALU 80W 1225	8400	80	4000	1204 x 51 x 102
FUCHSIA ALU 60W 1825	6300	60	4000	1825 x 51 x 102
FUCHSIA ALU 120W 1825	12600	120	4000	1825 x 51 x 102
FUCHSIA ALU 80W 2425	8400	80	4000	2425 x 51 x 102
FUCHSIA ALU 160W 2425	16800	160	4000	2425 x 51 x 102
FUCHSIA ALU 100W 3025	10500	100	4000	3025 x 51 x 102
FUCHSIA ALU 200W 3025	21000	200	4000	3025 x 51 x 102
FUCHSIA ALU 120W 3625	12600	120	4000	3625 x 51 x 102
FUCHSIA ALU 200W 3625	21000	200	4000	3625 x 51 x 102
FUCHSIA BLACK 20W 625	2100	20	4000	625 x 51 x 102
FUCHSIA BLACK 40W 625	4200	40	4000	625 x 51 x 102
FUCHSIA BLACK 40W 1225	4200	40	4000	1204 x 51 x 102
FUCHSIA BLACK 80W 1225	8400	80	4000	1204 x 51 x 102
FUCHSIA BLACK 60W 1825	6300	60	4000	1825 x 51 x 102
FUCHSIA BLACK 120W 1825	12600	120	4000	1825 x 51 x 102
FUCHSIA BLACK 80W 2425	8400	80	4000	2425 x 51 x 102
FUCHSIA BLACK 160W 2425	16800	160	4000	2425 x 51 x 102
FUCHSIA BLACK 100W 3025	10500	100	4000	3025 x 51 x 102
FUCHSIA BLACK 200W 3025	21000	200	4000	3025 x 51 x 102
FUCHSIA BLACK 120W 3625	12600	120	4000	3625 x 51 x 102
FUCHSIA BLACK 200W 3625	21000	200	4000	3625 x 51 x 102

Lighting and electrical parameters:

Light source	LED
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	50000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	0 ÷ +40
Driver	LED driver

Mechanical data:

Material	aluminum steel sheet
Color	anodized aluminum black *
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025