HONEY X

 $\left(\mathsf{IP}_{54} \right)$

Ð

ΊĶ₄)



Modern architectural luminary HONEY X features an original pattern of the simple form. HONEY X has a shape of "X" with curved finishes. HONEY X luminary is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

 $\langle \epsilon \rangle$

< 6Y

Parameters:

Name	Luminaire luminous flux [Im]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
HONEY X N 31W 726	2059	31	4000	726 x 1000 x 80
HONEY X N 62W 726	4118	62	4000	726 x 1000 x 80
HONEY X Z 31W 726	2059	31	4000	726 x 1000 x 80
HONEY X Z 62W 726	4118	62	4000	726 x 1000 x 80

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
CRI	>80
SDCM	3
Photobiological risk class	RGO
Operating temperature range [°C]	5÷30
Driver	LED Driver
Diver	DALI Driver *

Mechanical data:

aluminium
white
PLX opalized

