



HONEY HONEYCOMB



Modern architectural luminary HONEYCOMB (hexagon) features an original pattern of the simple form. HONEY COMB luminary is designed to interiors that require demanding architectural solutions. The shape of this luminary is modelled on actual honeycomb cell (hexagon with curved finishes). It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Parameters:

| Name | Luminaire luminous flux [lm] | Power of luminaire [W] | Color [K] | Dimensions A x B x H [mm] |
|------------------------------|------------------------------|------------------------|-------------|---------------------------|
| HONEY HONEYCOMB 25W 650 | 1496 / 1564 | 25 | 3000 / 4000 | 650 x 592 x 85 |
| HONEY HONEYCOMB 50W 650 | 2994 / 3128 | 50 | 3000 / 4000 | 650 x 592 x 85 |
| HONEY HONEYCOMB UD 75W 650 | 5724 | 75 | 4000 | 650 x 592 x 85 |
| HONEY HONEYCOMB 35W 900 | 2346 | 35 | 4000 | 900 x 809 x 85 |
| HONEY HONEYCOMB 70W 900 | 4692 | 70 | 4000 | 900 x 809 x 85 |
| HONEY HONEYCOMB UD 105W 900 | 8415 | 105 | 4000 | 900 x 809 x 85 |
| HONEY HONEYCOMB 50W 1045 | 3128 | 50 | 4000 | 1045 x 1178 x 85 |
| HONEY HONEYCOMB 92W 1045 | 6256 | 92 | 4000 | 1045 x 1178 x 85 |
| HONEY HONEYCOMB UD 138W 1045 | 11125 | 138 | 4000 | 1045 x 1178 x 85 |

Lighting and electrical parameters:

| | |
|-----------------------------------------|-----------------------------|
| Light source | LED |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 60000 |
| Lx/By | L80/B10 |
| CRI | >80 |
| SDCM | 3/4 |
| Photobiological risk class | RG0 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | DALI Driver LED Driver * |

Mechanical data:

| | |
|--------------|--------------|
| Material | aluminium |
| Color | white |
| Diffuser | PLX opalized |

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 08-05-2024