



Modern architectural luminaire HONEY L (line) features an original pattern of the simple form. HONEY L has a shape of line with curved finishes. HONEY L luminaire is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
HONEY L 8W 560	515	8	4000	560 x 80 x 80
HONEY L 16W 560	1029	16	4000	560 x 80 x 80
HONEY L 16W 1100	1029	16	4000	1100 x 80 x 80
HONEY L 32W 1100	2059	32	4000	1100 x 80 x 80
HONEY L 25W 1640	1544	25	4000	1640 x 80 x 80
HONEY L 50W 1640	3088	50	4000	1640 x 80 x 80

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical data:

Material	aluminium
Color	white
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024