## **IRIS 521**













The body of IRIS is made out of aluminium which is powder-lacquered with the use of weather condition resistant paint. The luminary is equipped with special holder to mount the product on poles and booms. The luminary's decline can be regulated to 15°. Its ingress protection is IP66. IRIS' diffuser is a transparent hardened glass. Photometry is received thanks to use of professional lens system.

## Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
IRIS 27W 521	3978 / 3894 / 3936	27	4000	521 x 260 x 186
IRIS 42W 521	5695 / 5574 / 5635	42	4000	521 x 260 x 186
IRIS 56W 521	7589   7428   7508	56	4000	521 x 260 x 186
IRIS 70W 521	10609 / 10383 / 10496	70	4000	521 x 260 x 186
IRIS 108W 521	15178 / 14855 / 15017	108	4000	521 x 260 x 186
IRIS 125W 521	17041 / 16679 / 16860	125	4000	521 x 260 x 186

## Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L70/B10
CRI	>70
SDCM	3
Operating temperature range [°C]	-40 ÷50
Driver	LED Driver

## Mechanical data:

Material	aluminium
Color	anthracite
Diffuser	ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024

