

IVY DOUBLE OD



Industrial luminaire IVY DOUBLE OD works ideally in production plants or other manufacturing facilities. There are two possible variants of mounting: suspended and eventually mounted on the ceiling (with use of specially prepared holders). IVY is made out of anodized aluminium. LED light sources are protected with hardened glass. The construction enables this luminaire to work in conditions where the temperature falls to -35 °C or reaches +50 °C. The additional regulated mounting bracket is optional. IVY luminaire has high ingress protection (IP66) and high protection against mechanical impact (IK10). IVY is recommended to industrial buildings, such as production hall, magazines, warehouses and also sports hall or trade areas.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
IVY DOUBLE OD 60W 308	10500 / 9975 / 9660 / 9177	60	4000	308 x 223 x 64
IVY DOUBLE OD 120W 608	21600 / 20520 / 19872 / 18878	120	4000	608 x 223 x 64
IVY DOUBLE OD 180W 908	32400 / 30780 / 29808 / 28317	180	4000	908 x 223 x 64
IVY DOUBLE OD 240W 1208	43200 / 41040 / 39744 / 37756	240	4000	1208 x 223 x 64
IVY DOUBLE OD 300W 1508	54000 / 51300 / 49680 / 47196	300	4000	1508 x 223 x 64

Lighting and electrical parameters:

Light source	LED
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B50
CRI	>70/>80
SDCM	3
Operating temperature range [°C]	-35 ÷ +50
Driver	LED driver

Mechanical data:

Material	aluminum
Color	anodized aluminum
	lenses 30°
	lenses 30° x 90°
	lenses 60°
	lenses 90°
	SM frosted glass
	ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025