



Industrial luminary IVY works ideally in production plants or other manufacturing facilities. There are two possible variants of mounting: suspended and eventually mounted on the ceiling (with use of specially prepared holders). IVY is made out of anodized aluminium. LED light sources are protected with hardened glass. The construction enables this luminary to work in conditions where the temperature falls to -35 °C or reaches +50 °C. The additional regulated mounting bracket is optional. IVY luminary has high ingress protection (IP66) and high protection against mechanical impact (IK10). IVY is recommended to industrial buildings, such as production hall, magazines, warehouses and also sports hall or trade areas.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
IVY OD 30W 308	5250 / 4987 / 4830 / 4588	30	4000	308 x 102 x 64
IVY OD 60W 608	10800 / 10260 / 9936 / 9439	60	4000	608 x 102 x 64
IVY OD 90W 908	16200 / 15390 / 14904 / 14158	90	4000	908 x 102 x 64
IVY OD 120W 1208	21600 / 20520 / 19872 / 18878	120	4000	1208 x 102 x 64
IVY OD 150W 1508	27000 / 25650 / 24840 / 23598	150	4000	1508 x 102 x 64

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B50
CRI	>70/>80
SDCM	3
Operating temperature range [°C]	-35 ÷ +50
Driver	LED driver

Mechanical data:

Material	aluminum anodized aluminum anthracite black white aluminum stainless steel grey *
Color	
Diffuser	lenses 30° lenses 30° x 90° lenses 60° lenses 90° SM frosted glass ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 01-08-2025