



Recessed luminaire LILY O P is made out of aluminium profile. The LILY MW luminaire is equipped with a multi-range power supply (MultiWatt), thanks to which the installer can select the power of the luminaire when connecting the luminaire, so the same luminaire can be used for many solutions, with several flux/power levels. LILY O P luminaires are recommended to interiors with professional characters, such as hotels, banks, offices etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
LILY O P MW 19W - 26W Ø165	#VALUE!	19 - 26,5	4000	Ø165 x 100
LILY O P PLX IP20/44 11W Ø100	839 / 864 / 923 / 896	11	3000 / 4000	Ø100 x 75
LILY O P PLX IP20/65 11W Ø100	839 / 864	11	3000 / 4000	Ø100 x 75
LILY O P PLX IP20/44 14W Ø100	1324 / 1363	14	3000 / 4000	Ø100 x 75
LILY O P PLX IP20/65 14W Ø100	1324 / 1363	14	3000 / 4000	Ø100 x 75
LILY O P PLX IP20/44 20W Ø165	2200 / 2265	20	3000 / 4000	Ø165 x 100
LILY O P PLX IP20/65 20W Ø165	2200 / 2265	20	3000 / 4000	Ø165 x 100
LILY O P PLX IP20/44 27W Ø165	2925 / 3011	27	3000 / 4000	Ø165 x 100
LILY O P PLX IP20/65 27W Ø165	3011 / 2925	27	4000 / 3000	Ø165 x 100
LILY O P PLX IP20/44 41W Ø165	4729	41	4000	Ø165 x 100
LILY O P MPRM IP20/44 11W Ø100	937 / 965	11	3000 / 4000	Ø100 x 75
LILY O P MPRM IP20/65 11W Ø100	937 / 965	11	3000 / 4000	Ø100 x 75
LILY O P MPRM IP20/44 14W Ø100	1479 / 1523	14	3000 / 4000	Ø100 x 75
LILY O P MPRM IP20/65 14W Ø100	1523 / 1479	14	4000 / 3000	Ø100 x 75
LILY O P MPRM IP20/44 20W Ø165	2306 / 2374	20	3000 / 4000	Ø165 x 100
LILY O P MPRM IP20/65 20W Ø165	2306 / 2374	20	3000 / 4000	Ø165 x 100
LILY O P MPRM IP20/44 27W Ø165	3065 / 3156	27	3000 / 4000	Ø165 x 100
LILY O P MPRM IP20/65 27W Ø165	3156 / 3065	27	4000 / 3000	Ø165 x 100
LILY O P MPRM IP20/44 41W Ø165	4955	41	4000	Ø165 x 100
LILY O P IP20/44 14W Ø100	1415 / 1457	14	3000 / 4000	Ø100 x 75
LILY O P IP20/65 14W Ø100	1457 / 1415	14	4000 / 3000	Ø100 x 75
LILY O P IP20/44 20W Ø165	2458 / 2531	20	3000 / 4000	Ø165 x 100
LILY O P IP20/65 20W Ø165	2458 / 2531	20	3000 / 4000	Ø165 x 100
LILY O P IP20/44 27W Ø165	3268 / 3364	27	3000 / 4000	Ø165 x 100
LILY O P IP20/65 27W Ø165	3364 / 3268	27	4000 / 3000	Ø165 x 100
LILY O P IP20/44 41W Ø165	5343	41	4000	Ø165 x 100

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	2
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver MultiWatt DALI Driver LED Driver *

Mechanical data:

Material	aluminium
Color	white
Diffuser	PLX opalized MPRM microprism ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024