

LILY OD O N



LILY OD N outdoor luminaire – it is intended for ceiling mounting on the outside of the building. Aluminium body, transparent glass, or transparent glass with additional milky diffuser. Intension – lighting entrances to buildings, arcades, terraces, balconies.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
LILY OD O N SH 19W	2546 / 2473	19	4000 / 3000	D120 x 168
LILY OD O N SH 13W	1855 / 1801	13	4000 / 3000	D120 x 168
LILY OD O N SH 9W	1320 / 1282	9.4	4000 / 3000	D120 x 168
LILY OD O N SH+PLX 19W	2250 / 2185	19	4000 / 3000	D120 x 168
LILY OD O N SH+PLX 13W	1639 / 1591	13	4000 / 3000	D120 x 168
LILY OD O N SH+PLX 9W	1167 / 1133	9.4	4000 / 3000	D120 x 168
LILY OD O N SH E27				D120 x 168

Lighting and electrical parameters:

Light source	LED/RETROFIT E27 (brak w komplecie)
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	2
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver No driver *

Mechanical data:

Material	aluminum
Color	white black *
Diffuser	ST transparent glass ST transparent glass + PLX

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025