



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
LILY SQ N PLX 11W 165	839 / 864	11	3000 / 4000	165 x 165 x 132
LILY SQ N PLX 14W 165	1363 / 1324	14	4000 / 3000	165 x 165 x 132
LILY SQ N PLX IP44 11W 165	839 / 864	11	3000 / 4000	165 x 165 x 132
LILY SQ N PLX IP44 14W 165	1324 / 1363	14	3000 / 4000	165 x 165 x 132
LILY SQ N MPRM 11W 165	937 / 965	11	3000 / 4000	165 x 165 x 132
LILY SQ N MPRM 14W 165	1523 / 1479	14	4000 / 3000	165 x 165 x 132
LILY SQ N MPRM IP44 11W 165	937 / 965	11	3000 / 4000	165 x 165 x 132
LILY SQ N MPRM IP44 14W 165	1523	14	4000	165 x 165 x 132
LILY SQ N 11W 165	896 / 923	11	3000 / 4000	165 x 165 x 132
LILY SQ N 14W 165	1415 / 1457	14	3000 / 4000	165 x 165 x 132
LILY SQ N IP44 11W 165	896 / 923	11	3000 / 4000	165 x 165 x 132
LILY SQ N IP44 14W 165	1457	14	4000	165 x 165 x 132
LILY SQ N PLX 20W 215	2200 / 2265	20	3000 / 4000	215 x 215 x 132
LILY SQ N PLX 27W 215	2925 / 3011	27	3000 / 4000	215 x 215 x 132
LILY SQ N PLX IP44 20W 215	2265	20	4000	215 x 215 x 132
LILY SQ N PLX IP44 27W 215	2925 / 3011	27	3000 / 4000	215 x 215 x 132
LILY SQ N MPRM 20W 215	2306 / 2374	20	3000 / 4000	215 x 215 x 132
LILY SQ N MPRM 27W 215	3156	27	4000	215 x 215 x 132
LILY SQ N MPRM IP44 27W 215	3156	27	4000	215 x 215 x 132
LILY SQ N 20W 215	2458 / 2531	20	3000 / 4000	215 x 215 x 132
LILY SQ N 27W 215	3364	27	4000	215 x 215 x 132
LILY SQ N IP44 20W 215	2531	20	4000	215 x 215 x 132
LILY SQ N IP44 27W 215	3268 / 3364	27	3000 / 4000	215 x 215 x 132

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	2
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver LED Driver *

Mechanical data:

Material	steel sheet
Color	white
Diffuser	PLX opalized MPRM microprism ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024