



LILY SQ adj N



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
LILY SQ adj N PLX 14W 165	1324 / 1363	14	3000 / 4000	165 x 165 x 132
LILY SQ adj N PLX 27W 215	2925 / 3011	27	3000 / 4000	215 x 215 x 170
LILY SQ adj N MPRM 14W 165	1479 / 1523	14	3000 / 4000	165 x 165 x 132
LILY SQ adj N MPRM 27W 215	3065 / 3156	27	3000 / 4000	215 x 215 x 170
LILY SQ adj N 14W 165	1415 / 1457	14	3000 / 4000	165 x 165 x 132
LILY SQ adj N 27W 215	3268 / 3364	27	3000 / 4000	215 x 215 x 170

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	2
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver *

Mechanical data:

Material	aluminium
Color	black white *
Diffuser	PLX opalized MPRM microprism ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024