

LILY SQ L2 P



Recessed luminaire LILY O P is made out of aluminium profile. LILY O P luminaires are recommended to interiors with professional characters, such as hotels, banks, offices etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions D x H [mm]
LILY SQ L2 P PLX 27W 268	2914 / 3001	27	3000 / 4000	268 x 165
LILY SQ L2 P MPRM 27W 268	2958 / 3047	27	3000 / 4000	268 x 165
LILY SQ L2 P 27W 268	2829 / 2914	27	3000 / 4000	268 x 165
LILY SQ L2 P PLX 27W 385	2914 / 3001	27	3000 / 4000	385 x 215
LILY SQ L2 P PLX 53W 385	5849 / 6022	53	3000 / 4000	385 x 215
LILY SQ L2 P MPRM 27W 385	2958 / 3047	27	3000 / 4000	385 x 215
LILY SQ L2 P MPRM 53W 385	6131 / 6313	53	3000 / 4000	385 x 215
LILY SQ L2 P 27W 385	2829 / 2914	27	3000 / 4000	385 x 215
LILY SQ L2 P 53W 385	6536 / 6702 / 6388	53	3000 / 4000	385 x 215

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
CRI	>80
SDCM	2
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver *

Mechanical data:

Material	aluminium
Color	black white *
Diffuser	PLX opalized MPRM microprism ST transparent glass

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024