

ORCHID C GK



Surface-mounted luminaire ORCHID C GK is made out of anodized aluminium profile. ORCHID luminaire is recommended for: office spaces, schools, universities or public administration buildings etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ORCHID C GK PLX 31W 1135	2880	31	4000	1142 x 80 x 72
ORCHID C GK PLX 41W 1135	3723	41	4000	1142 x 80 x 72
ORCHID C GK MPRM 31W 1135	3208	31	4000	1142 x 80 x 72
ORCHID C GK MPRM 41W 1135	4146	41	4000	1142 x 80 x 72

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver *

Mechanical data:

Material	aluminium anodized aluminium
Color	white black *
Diffuser	PLX opalized MPRM microprism

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024