



ORCHID OD N



Surface-mounted luminaire ORCHID is made out of anodized aluminium profile. ORCHID luminaire is recommended for: office spaces, schools, universities or public administration buildings etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ORCHID OD N PLX 13W 1135	1757	13.2	4000	1135 x 60 x 72
ORCHID OD N PLX 27W 1135	3458	27.2	4000	1135 x 60 x 72
ORCHID OD GARAGE 13W 575	2401 / 2268	13.6	4000 / 3000	575 x 60 x 72
ORCHID OD GARAGE 24W 1135	4018 / 3802	22.4	4000 / 3000	1135 x 60 x 72
ORCHID OD GARAGE 32W 1135	5576 / 5274	32.1	4000 / 3000	1135 x 60 x 72

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	-30 ÷ 40
Driver	LED driver

Mechanical data:

Material	aluminum anodized aluminum
Color	black anthracite white *
Diffuser	PLX opalized GARAGE optics

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 01-08-2025