




ORCHID N LINIA



Surface-mounted luminaire ORCHID is made out of anodized aluminium profile. ORCHID luminaire is recommended for: office spaces, schools, universities or public administration buildings etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ORCHID N LINIA MPRM 13W 0,6m	1886 / 1997	13.6	3000 / 4000	570 x 60 x 72 / 562 x 60 x 72
ORCHID N LINIA MPRM 20W 0,9m	2995 / 2829	20.4	4000 / 3000	850 x 60 x 72 / 842 x 60 x 72
ORCHID N LINIA MPRM 13W 1,2m	1919 / 2030	13.2	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA MPRM 27W 1,2m	3772 / 3994	27.2	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA MPRM 37W 1,2m	4985 / 5275	37.4	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA MPRM 34W 1,4m	4992 / 4716	34.1	4000 / 3000	1410 x 60 x 72 / 1402 x 60 x 72
ORCHID N LINIA MPRM 40W 1,7m	5991 / 5659	40.9	4000 / 3000	1690 x 60 x 72 / 1682 x 60 x 72
ORCHID N LINIA MPRM 47W 2,0m	6989 / 6602	47.7	4000 / 3000	1970 x 60 x 72 / 1962 x 60 x 72
ORCHID N LINIA MPRM 54W 2,2m	7545 / 7988	54.5	3000 / 4000	2250 x 60 x 72 / 2242 x 60 x 72
ORCHID N LINIA PLX 13W 0,6m	1633 / 1729	13.6	3000 / 4000	570 x 60 x 72 / 562 x 60 x 72
ORCHID N LINIA PLX 20W 0,9m	2449 / 2593	20.4	3000 / 4000	850 x 60 x 72 / 842 x 60 x 72
ORCHID N LINIA PLX 13W 1,2m	1661 / 1757	13.2	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA PLX 27W 1,2m	3266 / 3458	27.2	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA PLX 37W 1,2m	4316 / 4567	37.4	3000 / 4000	1130 x 60 x 72 / 1122 x 60 x 72
ORCHID N LINIA PLX 34W 1,4m	4322 / 4082	34.1	4000 / 3000	1410 x 60 x 72 / 1402 x 60 x 72
ORCHID N LINIA PLX 40W 1,7m	5187 / 4899	40.9	4000 / 3000	1690 x 60 x 72 / 1682 x 60 x 72
ORCHID N LINIA PLX 47W 2,0m	6051 / 5715	47.7	4000 / 3000	1970 x 60 x 72 / 1962 x 60 x 72
ORCHID N LINIA PLX 54W 2,2m	6532 / 6915	54.5	3000 / 4000	2250 x 60 x 72 / 2242 x 60 x 72

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	LED driver

Mechanical data:

Material	aluminum
Color	anodized aluminum black white *
Diffuser	MPRM micropism PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 01-08-2025