

ORCHID Raster SLIM N



Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ORCHID Raster SLIM N 65st. 575 BL	2110 / 1219 / 1993 / 1154	15 / 9	4000 / 3000	575 x 43 x 61
ORCHID Raster SLIM N 65st. 575 WH	2370 / 1369 / 2238 / 1297	15 / 9	4000 / 3000	575 x 43 x 61
ORCHID Raster SLIM N 90st. 575 BL	2084 / 1204 / 1968 / 1140	15 / 9	4000 / 3000	575 x 43 x 61
ORCHID Raster SLIM N 90st. 575 WH	2376 / 1373 / 2244 / 1300	15 / 9	4000 / 3000	575 x 43 x 61
ORCHID Raster SLIM N 65st. 855 BL	3163 / 1827 / 2989 / 1729	22 / 13	4000 / 3000	855 x 43 x 61
ORCHID Raster SLIM N 65st. 855 WH	3553 / 2052 / 3358 / 1943	22 / 13	4000 / 3000	855 x 43 x 61
ORCHID Raster SLIM N 90st. 855 BL	3124 / 1804 / 2952 / 1708	22 / 13	4000 / 3000	855 x 43 x 61
ORCHID Raster SLIM N 90st. 855 WH	3562 / 2057 / 3366 / 1948	22 / 13	4000 / 3000	855 x 43 x 61
ORCHID Raster SLIM N 65st. 1135 BL	4220 / 2438 / 3985 / 2309	28.5 / 17	4000 / 3000	1135 x 43 x 61
ORCHID Raster SLIM N 65st. 1135 WH	4741 / 2739 / 4477 / 2593	28.5 / 17	4000 / 3000	1135 x 43 x 61
ORCHID Raster SLIM N 90st. 1135 BL	4168 / 2408 / 3936 / 2280	28.5 / 17	4000 / 3000	1135 x 43 x 61
ORCHID Raster SLIM N 90st. 1135 WH	4753 / 2746 / 4488 / 2600	28.5 / 17	4000 / 3000	1135 x 43 x 61

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L80/B10
CRI	>80
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical data:

Material	aluminium
Color	black white *
Diffuser	UGR 65° raster UGR 90° raster

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024