

RODA BASIC 1784



Industrial luminaire RODA BASIC 1784 FOSNOVA is made out of polycarbonate lacquered white. The diffuser is made from opalized PMMA. The colour temperature is 4000 K and colour rendering index CRI > 80. The luminaire works in temperature fluctuating from -30 °C to +40 °C. Its ingress protection is IP65 and the protection against mechanical impacts is IK08. The product has increased durability and is recommended for production halls, magazines, warehouses and other industrial spaces that are much more demanding.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
RODA BASIC 1784 18W	1800	18	4000	633 x 68 x 55 / 666 x 68 x 55
RODA BASIC 1784 36W	3600	36	4000	1233 x 68 x 55 / 1266 x 68 x 55
RODA BASIC 1784 50W	5000	50	4000	1533 x 68 x 55 / 1566 x 68 x 55

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	45000
Lx/By	L70/B50
CRI	>80
SDCM	3
Operating temperature range [°C]	-30 ÷ +40
Driver	LED Driver

Mechanical data:

Material	aluminium
Color	white
Diffuser	PLX opalized

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024