

ROSE MED CLIP-IN



Parameters:

| Name                                    | Luminaire luminous flux [lm] | Power of luminaire [W] | Color [K] | Dimensions A x B x H [mm] |
|-----------------------------------------|------------------------------|------------------------|-----------|---------------------------|
| ROSE MED P CLIP-IN CRI90 50W 600        | 5131 / 5828                  | 50                     | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN CRI90 65W 600        | 6842 / 7771                  | 65                     | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN CRI90 83W 600        | 8552 / 9713                  | 83                     | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN SHMR CRI90 600       | 5957 / 7943 / 9928           | 50 / 65 / 83           | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN CRI90 SH BIO 50W 600 | 4851 / 5827                  | 50                     | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN CRI90 SH BIO 65W 600 | 6468 / 7769                  | 65                     | 4000      | 595 x 595 x 80            |
| ROSE MED P CLIP-IN CRI90 SH BIO 83W 600 | 8085 / 9711                  | 83                     | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN 37W 600          | 4787 / 5437                  | 37                     | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN 47W 600          | 6383 / 7250                  | 47                     | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN 60W 600          | 7979 / 9062                  | 60.3                   | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN SH BIO 37W 600   | 4576 / 5436                  | 37                     | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN SH BIO 47W 600   | 6102 / 7248                  | 47                     | 4000      | 595 x 595 x 80            |
| ROSE MED PRO P CLIP-IN SH BIO 60W 600   | 7627 / 9060                  | 60.3                   | 4000      | 595 x 595 x 80            |

Lighting and electrical parameters:

|                                  |                             |
|----------------------------------|-----------------------------|
| Light source                     | LED                         |
| Voltage                          | 220-240 V, 50-60 Hz         |
| Lifetime of LED sources [h]      | 150000                      |
| Lx/By                            | L70/B50/L80/B10             |
| CRI                              | >90/>80                     |
| SDCM                             | 3                           |
| Operating temperature range [°C] | 5 ÷ 30                      |
| Driver                           | DALI Driver<br>LED Driver * |

Mechanical data:

|          |                                                                                                                                                                                                 |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material | steel sheet + antibacterial paint<br>steel sheet                                                                                                                                                |
| Color    | white                                                                                                                                                                                           |
| Diffuser | MPRM SH microprism tempered glass<br>SHM tempered milky glass<br>SHM tempered milky glass with anti-reflective coating<br>MPRM SH microprism tempered glass BIO<br>SHM tempered milky glass BIO |

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024