

ROSE P CLIP-IN



CLEAN luminaire ROSE is intended for module dropped ceilings and is made out of white-lacquered steel plate. Application: operating theatre, doctors' surgery, laboratory.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
ROSE P CLIP-IN CRI90 50W 600	5778 / 5544 / 5462 / 5828	50	4000	595 x 595 x 80
ROSE P CLIP-IN CRI90 65W 600	7704 / 7392 / 7283 / 7771	65	4000	595 x 595 x 80
ROSE P CLIP-IN CRI90 83W 600	9630 / 9240 / 9103 / 9713	83	4000	595 x 595 x 80
ROSE P CRI90 99W 1200	11656 / 11088	99	4000	1195 x 595 x 80

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L70/B50
CRI	>90
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	DALIDriver LED Driver *

Mechanical data:

Material	steel sheet
Color	white
	MPRM microprism
Diffuser	MPRM SH microprism tempered glass
	PLX opalized
	SHM tempered milky glass

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024