

SNOWDROP N



Surface-mounted luminaire SNOWDROP N is made from white powder-lacquered steel plate. SNOWDROP N shines indirectly, its attuned light distribution („soft light“) which prevents from reflections to appear on the computer screens or other devices. This leads to an increase in the comfort of being in work stand rooms. SNOWDROP N luminary is recommended for offices, conference halls, IT suits, schools, universities, any kind of public buildings etc.

Parameters:

Name	Luminaire luminous flux [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
SNOWDROP N 24W 600	3491 / 3676	25	3000 / 4000	600 x 610 x 70
SNOWDROP N 36W 600	5185 / 5460	36.5	3000 / 4000	600 x 610 x 70

Lighting and electrical parameters:

Light source	LED
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
CRI	>80
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver DALI Driver *

Mechanical data:

Material	steel sheet
Color	white
Diffuser	MPRM microprism

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024