



Description

Modern architectural luminaire HONEY SQ (square) features an original pattern of the simple form. HONEY SQ has a shape of a square with curved finishes. HONEY SQ luminaire is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Basic information

Family: HONEY SQ
Product: HONEY SQ Z TW PLX DALI WH 827-865 ZAW-1,5M 28 660
Index: BLS0000000090
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	5400
LED power [W]	47
Luminaire luminous flux [lm]	2808
Power of luminaire [W]	52
Luminaire's light efficiency [lm/W]	54
Color of the light [K]	2700 ÷ 6500
CRI	>80
SDCM (LED sources)	4
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver

Mechanical parameters:

Assembly	pendant
Material	aluminium
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Dimensions [mm]	660 x 660 x 85



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024