#### **Product card**

# **HONEY SQ**



#### Description

Modern architectural luminary HONEY SQ (square) features an original pattern of the simple form. HONEY SQ has a shape of a square with curved finishes. HONEY SQ luminary is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

### Basic information

Family: Product: Index: Pictograms:

HONEY SQ Z UD PLX WH 840 ZAW-1,5M 146 1200 BLS000000094




## Lighting and electrical parameters

**HONEY SQ** 


Light source	LED
Luminous flux LED [Im]	# VALUE!
LED power [W]	53/112
Luminaire luminous flux [lm]	14612
Power of luminaire [W]	185
Luminaire's light efficiency [lm/W]	79
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	4
Photobiological risk class (IEC/EN 62471)	RGO
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5÷30
Driver	LED Driver
Color of the light [K] CRI SDCM (LED sources) Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	4000 >80 4 RGO I IP54 220-240 V, 50-60 Hz 60000 L80/B10 5÷30

## Mechanical parameters:

	popdant
Assembly	pendant
Material	aluminium
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Dimensions [mm]	1200 x 1200 x 85



### A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024

