



Description

Modern architectural luminaire HONEY SQ (square) features an original pattern of the simple form. HONEY SQ has a shape of a square with curved finishes. HONEY SQ luminaire is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Basic information

Family: HONEY SQ  
Product: HONEY SQ Z UD PLX WH 840 ZAW-1,5M 74 660  
Index: BLS0000000095  
Pictograms:




Lighting and electrical parameters


|   |                     |
|---|---------------------|
| Light source                              | LED                 |
| Luminous flux LED [lm]                    | #VALUE!             |
| LED power [W]                             | 28/56               |
| Luminaire luminous flux [lm]              | 7404                |
| Power of luminaire [W]                    | 95                  |
| Luminaire's light efficiency [lm/W]       | 78                  |
| Color of the light [K]                    | 4000                |
| CRI                                       | >80                 |
| SDCM (LED sources)                        | 4                   |
| Photobiological risk class (IEC/EN 62471) | RG0                 |
| Protection against electric shock         | I                   |
| Protection degree                         | IP54                |
| Voltage                                   | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h]               | 60000               |
| Lx/By                                     | L80/B10             |
| Operating temperature range [°C]          | 5 ÷ 30              |
| Driver                                    | LED Driver          |

Mechanical parameters:

|                  |                |
|------------------|----------------|
| Assembly         | pendant        |
| Material         | aluminium      |
| Color            | white          |
| Diffuser         | PLX opalized   |
| Impact resistant | IK04           |
| Dimensions [mm]  | 660 x 660 x 85 |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024