Product card

HONEY HONEYCOMB



Description

Modern architectural luminary HONEYCOMB (hexagon) features an original pattern of the simple form. HONEY COMB luminary is designed to interiors that require demanding architectural solutions. The shape of this luminary is modelled on actual honeycomb cell (hexagon with curved finishes). It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Basic information

Family: Product: Index: Pictograms: HONEY HONEYCOMB HONEY HONEYCOMB Z PLX DALI WH 840 ZAW-1,5M 62 1043 BLS000000018




Lighting and electrical parameters


Light source	LED
Luminous flux LED [Im]	11880
LED power [W]	84
Luminaire luminous flux [lm]	6256
Power of luminaire [W]	92
Luminaire's light efficiency [lm/W]	68
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RGO
Protection against electric shock	L
Protection degree	IP54
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5÷30
Driver	DALI Driver

Mechanical parameters:

Assembly	popdant
Assembly	pendant
Material	aluminium
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Dimensions [mm]	1045 x 1178 x 85



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024

