Product card



Description

Modern architectural luminary HONEY L (line) features an original pattern of the simple form. HONEY L has a shape of line with curved finishes. HONEY L luminary is designed to interiors that require demanding architectural solutions. It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Basic information

Family: Product: Index: Pictograms:

HONEY L Z PLX WH 840 ZAW-1,5M 20 1100 BLS0000000032




Lighting and electrical parameters

HONEY L


| Light source | LED |
|---|---------------------|
| Luminous flux LED [lm] | 3960 |
| LED power [W] | 28 |
| Luminaire luminous flux [lm] | 2059 |
| Power of luminaire [W] | 32 |
| Luminaire's light efficiency [lm/W] | 64 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RGO |
| Protection against electric shock | 1 |
| Protection degree | IP54 |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 60000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5÷30 |
| Driver | LED Driver |
| | |

Mechanical parameters:

| Assembly | pendant |
|------------------|----------------|
| Material | aluminium |
| Color | white |
| Diffuser | PLXopalized |
| Impact resistant | IK04 |
| Dimensions [mm] | 1100 x 80 x 80 |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024

