



Description

Surface-mounted luminaire ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: **ORCHID N**  
Product: **ORCHID N MPRM BL 840 73 2255**  
Index: **BLS0000000636**  
Pictograms:



Lighting and electrical parameters

Light source	LED
<b>Luminous flux LED [lm]</b>	<b>8968</b>
LED power [W]	44
<b>Luminaire luminous flux [lm]</b>	<b>7386</b>
Power of luminaire [W]	48
<b>Luminaire's light efficiency [lm/W]</b>	<b>154</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	3
<b>Photobiological risk class (IEC/EN 62471)</b>	<b>RG0</b>
Protection against electric shock	I
<b>Protection degree</b>	<b>IP44</b>
Voltage	220-240 V, 50-60 Hz
<b>Lifetime of LED sources [h]</b>	<b>150000</b>
Lx/By	L80/B50
<b>Operating temperature range [°C]</b>	<b>5 ÷ 30</b>
Driver	LED Driver

Mechanical parameters:

Assembly	ceiling mounted
<b>Material</b>	<b>aluminium</b>
Color	black
<b>Diffuser</b>	<b>MPRM microprism</b>
Impact resistant	IK06
<b>Weight [kg]</b>	<b>3.65</b>
Dimensions [mm]	2255 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 14-05-2024