




## Description

Industrial luminaire IVY DOUBLE works ideally in production plants or other manufacturing facilities. There are two possible variants of mounting: suspended and eventually mounted on the ceiling (with use of specially prepared holders). IVY is made out of anodized aluminium. LED light sources are protected with hardened glass. The construction enables this luminaire to work in conditions where the temperature falls to  $-35\text{ }^{\circ}\text{C}$  or reaches  $+50\text{ }^{\circ}\text{C}$ . The additional regulated mounting bracket is optional. IVY luminaire has high ingress protection (IP66) and high protection against mechanical impact (IK10). IVY is recommended to industrial buildings, such as production hall, magazines, warehouses and also sports hall or trade areas.

## Basic information

Family:	<b>IVY DOUBLE</b>
Product:	<b>IVY DOUBLE Z OPT60 IP66 840 205 608</b>
Index:	<b>BLS0000001485</b>
Pictograms:	




## Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>20520</b>
Power of luminaire [W]	120
<b>Luminaire's light efficiency [lm/W]</b>	<b>171</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	3
<b>Protection against electric shock</b>	<b>I</b>
Protection degree	IP66
<b>Voltage</b>	<b>220-240V, 50-60Hz</b>
Lifetime of LED sources [h]	80000
<b>Lx/By</b>	<b>L80/B50</b>
Operating temperature range [ $^{\circ}\text{C}$ ]	$-35 \div +50$
<b>Driver</b>	<b>LED driver</b>

## Mechanical parameters:

Assembly	pendant
<b>Material</b>	<b>aluminum</b>
Color	anodized aluminum
<b>Diffuser</b>	<b>lenses 60°</b>
Impact resistant	IK10
<b>Dimensions [mm]</b>	<b>608 x 223 x 64</b>



## A graph of light

