



Description

Industrial luminaire IVY ZK is made out of aluminium and its diffuser from transparent polycarbonate. IVY ZK is perfect for special spaces that might be subject to any kind of damage or acts of vandalism. The high protection against mechanical impacts IK10 makes IVY ZK a perfect product for: prisons and its cells, mental hospitals, police custodies, youth detention centres, but also subways or circulation areas.

Basic information

Family: IVY ZK
Product: IVY ZK N PC-T 840 21 201
Index: BLS0000001517
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	2100
Power of luminaire [W]	15
Luminaire's light efficiency [lm/W]	140
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP20
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B50
Operating temperature range [°C]	-35 ÷ +50
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	white
Diffuser	PC transparent polycarbonate
Impact resistant	IK10
Dimensions [mm]	201 x 67 x 102



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 18-08-2025