



## Description

Recessed luminaire LILY O P is made out of aluminium profile. LILY O P luminaires are recommended to interiors with professional characters, such as hotels, banks, offices etc.

## Basic information

Family:	<b>LILY SQ L2 P</b>
Product:	<b>LILY SQ L2 P MPRM WH 840 28 385</b>
Index:	<b>BLS0000001679</b>
Pictograms:	



## Lighting and electrical parameters

Light source	LED
<b>Luminous flux LED [lm]</b>	<b>3922</b>
LED power [W]	24.6
<b>Luminaire luminous flux [lm]</b>	<b>3047</b>
Power of luminaire [W]	27
<b>Luminaire's light efficiency [lm/W]</b>	<b>113</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	2
<b>Photobiological risk class (IEC/EN 62471)</b>	<b>RG0</b>
Protection against electric shock	I
<b>Protection degree</b>	<b>IP20</b>
Voltage	220-240 V, 50-60 Hz
<b>Lifetime of LED sources [h]</b>	<b>100000</b>
Lx/By	L80/B10
<b>Operating temperature range [°C]</b>	<b>5 ÷ 30</b>
Driver	LED Driver

## Mechanical parameters:

Assembly	recessed into the modular and plasterboard ceiling
<b>Material</b>	<b>aluminium</b>
Color	white
<b>Diffuser</b>	<b>MPRM microprism</b>
Impact resistant	IK04
<b>Dimensions [mm]</b>	<b>385 x 215</b>
Mounting hole [mm]	370 x 200

## A graph of light

