



Description

Recessed luminaire LILY O P is made out of aluminium profile. LILY O P luminaires are recommended to interiors with professional characters, such as hotels, banks, offices etc.

Basic information

Family: LILY SQ L2 P
Product: LILY SQ L2 P BL 840 26 385
Index: BLS0000001683
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	3922
LED power [W]	24.6
Luminaire luminous flux [lm]	2914
Power of luminaire [W]	27
Luminaire's light efficiency [lm/W]	108
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into the modular and plasterboard ceiling
Material	aluminium
Color	black
Diffuser	ST transparent glass
Impact resistant	IK04
Dimensions [mm]	385 x 215
Mounting hole [mm]	370 x 200

A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024