



Description

Recessed luminaire LILY O P is made out of aluminium profile. LILY O P luminaires are recommended to interiors with professional characters, such as hotels, banks, offices etc.

Basic information

Family: LILY O P
Product: LILY O P PLX WH IP20/65 840 29 D165
Index: BLS0000001610
Pictograms:



Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	3935
LED power [W]	24
Luminaire luminous flux [lm]	3011
Power of luminaire [W]	27
Luminaire's light efficiency [lm/W]	112
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	2
Beam angle [°]	102
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into the modular and plasterboard ceiling
Material	aluminium
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Weight [kg]	0.95
Dimensions [mm]	Ø165 x 100
Mounting hole [mm]	Ø140



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024