



Description

Recessed luminaire SNOWDROP P is a lighting luminary that can be installed in dropped module ceiling 600x600 mm or in plasterboard ceiling (additional accessory required). SNOWDROP P is made out of steel plate which is white powder-lacquered. SNOWDROP P luminaire has the most modern highly-efficient LED light sources, whose lifespan is longer than 60.000 hours. SNOWDROP P features indirect shining that increases the comfort of being in a particular room.

Basic information

Family: SNOWDROP P
Product: SNOWDROP P MPRM WH 830 34 1196
Index: BLS0000002063
Pictograms:



Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	4258
LED power [W]	22
Luminaire luminous flux [lm]	3439
Power of luminaire [W]	24
Luminaire's light efficiency [lm/W]	143
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into the modular ceiling
Material	steel sheet
Color	white
Diffuser	MPRM microprism
Impact resistant	IK04
Weight [kg]	2.96
Dimensions [mm]	1196 x 296 x 55

A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024