




Description

Recessed luminaire SNOWDROP P is a lighting luminaire that can be installed in dropped module ceiling 600x600 mm or in plasterboard ceiling (additional accessory required). SNOWDROP P is made out of steel plate which is white powder-lacquered. SNOWDROP P luminaire has the most modern highly-efficient LED light sources, whose lifespan is longer than 60.000 hours. SNOWDROP P features indirect shining that increases the comfort of being in a particular room.

Basic information

Family:	SNOWDROP P
Product:	SNOWDROP P MPRM WH DALI 840 54 596
Index:	BLS0000002070
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	5433
Power of luminaire [W]	36.5
Luminaire's light efficiency [lm/W]	149
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	DALI driver

Mechanical parameters:

Assembly	recessed into the modular ceiling
Material	steel sheet
Color	white
Diffuser	MPRM microprism
Impact resistant	IK04
Weight [kg]	2.96
Dimensions [mm]	596 x 596 x 55



A graph of light