



Description

Industrial luminaire IVY DOUBLE OD works ideally in production plants or other manufacturing facilities. There are two possible variants of mounting: suspended and eventually mounted on the ceiling (with use of specially prepared holders). IVY is made out of anodized aluminium. LED light sources are protected with hardened glass. The construction enables this luminaire to work in conditions where the temperature falls to $-35\text{ }^{\circ}\text{C}$ or reaches $+50\text{ }^{\circ}\text{C}$. The additional regulated mounting bracket is optional. IVY luminaire has high ingress protection (IP66) and high protection against mechanical impact (IK10). IVY is recommended to industrial buildings, such as production hall, magazines, warehouses and also sports hall or trade areas.

Basic information

Family:	IVY DOUBLE OD
Product:	IVY DOUBLE OD K OPT 30x90 IP66 740 540 1508
Index:	BLS0000002152
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	54000
Power of luminaire [W]	300
Luminaire's light efficiency [lm/W]	180
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP66
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B50
Operating temperature range [$^{\circ}\text{C}$]	$-35 \div +50$
Driver	LED driver

Mechanical parameters:

Assembly	wall-mounted
Material	aluminum
Color	anodized aluminum
Diffuser	lenses 30° x 90°
Impact resistant	IK10
Dimensions [mm]	1508 x 223 x 64



A graph of light

