


## Description

Outdoor architectural luminaire NEMESIA is perfect for creating lighting effects on elevations and highlighting selected features. This luminaire is mounted using assembly box included in the set. The body of NEMESIA is made from aluminium and is lacquered in specialistic facade paint that is resistant to any kind of weather. Different LED colours are also possible. NEMESIA luminaire is highly energy-efficient thanks to its high-performance components. Product features high ingress protection IP65. Its ergonomic and functional shape enables to use of NEMESIA in practically every kind of building. The assembly and access to the inside is very easy. It is ideal to emphasize the character of the building, it plays a role of secondary lighting, which makes NEMESIA a great outdoor lighting decoration with a simple form and aesthetic look.

## Basic information

Family:	<b>NEMESIA OD</b>
Product:	<b>NEMESIA OD 1X1,7W 24° GR IP65 840 1100</b>
Index:	<b>BLS0000002270</b>
Pictograms:	




## Lighting and electrical parameters

Light source	LED
<b>LED power [W]</b>	<b>2</b>
Luminaire luminous flux [lm]	144
<b>Power of luminaire [W]</b>	<b>3</b>
Luminaire's light efficiency [lm/W]	48
<b>Color of the light [K]</b>	<b>4000</b>
CRI	>80
<b>SDCM (LED sources)</b>	<b>5</b>
Beam angle [°]	24
<b>Protection against electric shock</b>	<b>I</b>
Protection degree	IP65
<b>Voltage</b>	<b>220-240 V, 50-60 Hz</b>
Lifetime of LED sources [h]	50000
<b>Lx/By</b>	<b>L70/B50</b>
Operating temperature range [°C]	-25 ÷ 30
<b>Driver</b>	<b>LED Driver</b>

## Mechanical parameters:

Assembly	wall-mounted
<b>Material</b>	<b>aluminium</b>
Color	gray
<b>Diffuser</b>	<b>PC transparent polycarbonate</b>
Impact resistant	IK09
<b>Dimensions [mm]</b>	<b>100 x 100 x 94</b>



## A graph of light