




Description

Outdoor architectural luminaire NEMESIA is perfect for creating lighting effects on elevations and highlighting selected features. This luminaire is mounted using assembly box included in the set. The body of NEMESIA is made from aluminium and is lacquered in specialistic facade paint that is resistant to any kind of weather. Different LED colours are also possible. NEMESIA luminaire is highly energy-efficient thanks to its high-performance components. Product features high ingress protection IP65. Its ergonomic and functional shape enables to use of NEMESIA in practically every kind of building. The assembly and access to the inside is very easy. It is ideal to emphasize the character of the building, it plays a role of secondary lighting, which makes NEMESIA a great outdoor lighting decoration with a simple form and aesthetic look.

Basic information

Family:	NEMESIA OD_
Product:	NEMESIA OD 1X2,4W 5°-21° GR IP65 830 1100
Index:	BLS0000002275z
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	151
Power of luminaire [W]	4
Luminaire's light efficiency [lm/W]	38
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	5
Beam angle [°]	5-21
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	wall-mounted
Material	aluminum
Color	grey
Diffuser	PC transparent polycarbonate
Impact resistant	IK09
Dimensions [mm]	100 x 100 x 94



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 26-09-2025