Product card

NEMESIA OD



Description

Outdoor architectural luminary NEMESIA. The body of NEMESIA is made from aluminium and is lacquered in specialistic facade paint that is resistant to any kind of weather. Different LED colours are also possible. NEMESIA luminary is highly energy-efficient thanks to its high-performance components. Product features high ingress protection IP65. Its ergonomic and functional shape enables to use of NEMESIA in practically every kind of building. The assembly and access to the inside is very easy. It is ideal to emphasize the character of the building, it plays a role of secondary lighting, which makes NEMESIA a great outdoor lighting decoration with a simple form and aesthetic look.

Basic information

Family: Product: Index: Pictograms:

NEMESIA OD 4X2,4W 5°-21° GR IP65 840 7 100 BLS0000002306




Lighting and electrical parameters

NEMESIA OD

Light source	LED
LED power [W]	10
Luminaire luminous flux [Im]	748
Power of luminaire [W]	12
Luminaire's light efficiency [Im/W]	62
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	5
Beam angle [°]	5-21
Protection against electric shock	1
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-25 ÷30
Driver	LED Driver

Mechanical parameters:

all-mounted
aluminium
gray
carbonate
IK09
0 x 100 x 94
,



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024