




Description

Outdoor luminaire PANSY shines with the usage of highly-efficient LED lights sources. Its case and body are made from aluminium cast. Its transparent polycarbonate diffuser has high protection against mechanical impact IK09. PANSY luminaire has also high ingress protection IP66, which classifies it as resistant to any kind of weather, so it keeps its primary, aesthetic and clean appearance during exploitation. PANSY is recommended for parks, gardens, plazas, market squares or other open spaces.

Basic information

Family: **PANSY OD**
 Product: **PANSY OD IP66 ANT 740 41 D480**
 Index: **BLS0000002308**
 Pictograms:




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	4194
Power of luminaire [W]	24.4
Luminaire's light efficiency [lm/W]	172
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP66
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	102000
Lx/By	L90/B10
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	mounted on poles with brackets
Material	aluminum
Color	anthracite
Diffuser	ST transparent glass
Impact resistant	IK09
Weight [kg]	7.40
Dimensions [mm]	Ø465(/480) x 525



A graph of light